



- Engines up to 4 cylinders supported
- Cooperation with external Scanner TECH-OBD
- TECH and Standard tuning algorithm
- Self diagnosis of faults and defects
- Full short circuit and overload protection
- Compatible with Valvetronic and Rotary engines
- 48-pin connector
- Composite casing

TECHNICAL SPECIFICATION:

- Supply voltage: min. 10 [V] max. 16 [V]
- Quiescent current: <10 mA
- Max. current: 15 [A]
- Temperature Range: -20 [° C] to 110 [° C]

TECH-200 Controller Series

TYPE: LPG/CNG Injection Controllers**MODEL:** TECH-204, TECH-224

TECH-200 controller series - a modern microprocessor controllers with the 48-pin bundle, for up to 4-cylinders engines. It combines advanced technology with ergonomics. A processor which controls calibration, autotuning and continuous monitoring system is locked in a small body made of tecamid.

INSTALLATION INSTRUCTION:

The controller should be attached permanently to the fixed vehicle's parts, away from high voltage cables, in a place that is not exposed to the high temperatures (up to 110 °C) and water, with the socket directed downwards (except in cases where the producer's recommendation is to assembly it in a different way).

All wires must be isolated and led in such a way, as not to interfere with the operation of other vehicle components and were not close to moving vehicle's parts.

Electrical connections should be soldered and isolated.